



## Profibus Signal Cables

0975 254 131



0975 254 131/...M

Single-ended Profibus signal cable, M12 female right angle connector B coded, molded on one side, 360° shielding connected to knurled nut.

0975 254 132



0975 254 132/...M

Single-ended Profibus signal cable, M12 male right angle connector B coded, molded on one side, 360° shielding connected to knurled nut.

0975 254 130



0975 254 130/...M

Double-ended cord set, 360° shielding, M12 male right angle connector to M12 female right angle connector, 5 poles, B-coding.

0975 254 134




0975 254 134/...M

Double-ended cord set, 360° shielding, M12 male right angle connector to M12 female straight connector, 5 poles, B-coding.

### Pin Assignment

M12 male/female connector, 5 poles



- 1 = n.c.
- 2 = Line A - green
- 3 = n.c.
- 4 = Line B - red
- 5 = n.c.

Part Number	Standard Cable Lengths	UL	IP67	C	Shielding
0975 254 130/...M	0.3 M   0.6 M   1 M   2 M   3 M   5 M   10 M	UL	IP67	C	Shielding
0975 254 131/...M	2 M   5 M   10 M	UL	IP67	C	Shielding
0975 254 132/...M	2 M   5 M   10 M	UL	IP67	C	Shielding
0975 254 134/...M	1 M   2 M   3 M	UL	IP67	C	Shielding