





[Article Page](#)

Product Description **capacitive sensor DC**

Name	SC20-M30MB90-DPÖ-V2
Order number	08323302022
Switching distance	20 mm
Mounting	 shielded
Switch type	 N.C.
Signal Type	DC PNP
Connection	 Connector

Connection diagramm



Dimension (in mm)	fine-pitch thread M30 x 90
-------------------	----------------------------

Technical Specification

Operating voltage	10 - 30 VDC
Max. ripple	≤ 10 %
Voltage drop	2 V
Max. load current	200 mA
No load current	≤ 10 mA
Leakage current	≤ 10 µA
Switching frequency	100
Switching hysteresis	≤ 15 %
Operating temperature	-25 ° C to 70 ° C
Temperature drift	≤ 10 %
Repeat accuracy	≤ 5 %
Switching state	LED
Digital output	
Short-circuit proof	yes
Overload protection	yes
Reverse voltage protection	yes
Protection category	IP67
EMC-level	DIN EN 60947-5-2:2008
Material active face	PBT
Termination	Connector M12 4pol



SC20-M30MB90-DPÖ-V2

Pulsotronic GmbH & Co. KG Neue Schichtstraße 14b 09366 Niederdorf Deutschland +49 (0)37296 930-200

Errors and omissions exceptet