





[Article Page](#)

Product Description **fibre optic device**

Name	KOLL-Q30KB-DPA-V1-RT
Order number	08365821064
Matchcode	9882-1064
Switch type	 Changeover
Signal Type	DC PNP
Illuminant	 Red light 660 nm
Connection	 Connector

Connection diagramm



Dimension (in mm)	15 x 30 x 30
-------------------	--------------

Technical Specification

Signal type	Fibre-optic sensor
Operating voltage	10 - 36 V DC
Max. load current	200 mA
No load current	< 15 mA
Switching frequency	1000
Operating temperature	-25 ° C to 55 ° C
Swiching state	LED
Digital output	
Sensitivity adjustable	ja
Sensing range adjustable	nein
Short-circuit proof	yes
Overload protection	yes
Reverse voltage protection	yes
Protection category	IP67
EMC-level	DIN EN 60947-5-2:2008
Housing material	Plastic
Termination	Connector M8 4pol
Notes	max. Laststrom 200mA (bei antivalent Summe beider Ausgänge)



KOLL-Q30KB-DPA-V1-RT

Pulsotronic GmbH & Co. KG Neue Schichtstraße 14b 09366 Niederdorf Deutschland +49 (0)37296 930-200

Errors and omissions exceptet