


[Article Page](#)


Product Description

inductive sensor DC



Name	KJ10-M30MB40-DNS
Order number	08317664100
Matchcode	9966-4100
Switching distance	10 mm
Mounting	 shielded
Switch type	 N.O.
Signal Type	DC NPN
Connection	 Cable

Connection diagramm



Dimension (in mm)	fine-pitch thread M30 x 40
-------------------	----------------------------

Technical Specification

Operating voltage	10 - 30 VDC
Max. ripple	$\leq 10 \%$
Voltage drop	2,4 V
Max. load current	200 mA
No load current	$\leq 13 \text{ mA}$
Leakage current	$\leq 10 \mu\text{A}$
Switching frequency	500 Hz
Switching hysteresis	$\leq 15 \%$

Operating temperature	-25 ° C to 70 ° C
Temperature drift	≤ 10 %
Repeat accuracy	≤ 10 %
Switching state	LED
Short-circuit proof	yes
Overload protection	yes
Reverse voltage protection	yes
Protection category	IP67
EMC-level	DIN EN 60947-5-2: 2008
Housing material	Brass, nickel plated
Material active face	PA 6.6 sw
Cable length	2 m
Utilisation category	DC 13
Cable material	PVC grau LIYY
Cable cross	3x0.34 mm ²

Errors and omissions excepted