


[Article Page](#)


Product Description

inductive sensor DC



Name	KJ8-M18MB60-DPS
Order number	08317643900
Matchcode	9964-3900
Switching distance	8 mm
Mounting	 shielded
Switch type	 N.O.
Signal Type	DC PNP
Connection	 Cable

Connection diagramm



Dimension (in mm)	fine-pitch thread M18 x 60
-------------------	----------------------------

Technical Specification

Operating voltage	10 - 30 V DC
Max. ripple	$\leq 10 \%$
Voltage drop	2,4 V
Max. load current	200 mA
No load current	$\leq 10 \text{ mA}$
Leakage current	$\leq 10 \mu\text{A}$
Switching frequency	500 Hz
Switching hysteresis	$\leq 15 \%$

Operating temperature	-25 ° C to 70 ° C
Temperature drift	≤ 10 %
Repeat accuracy	≤ 10 %
Switching state	LED
Short-circuit proof	yes
Overload protection	yes
Reverse voltage protection	yes
Protection category	IP67
EMC-level	DIN EN 60947-5-2: 2008
Housing material	Brass, nickel plated
Material active face	Schulamid
Cable length	2 m
Utilisation category	DC 13
Cable material	^PVC grau LIYY
Cable cross	3x0.34 mm ²

Errors and omissions excepted