



[Article Page](#)


Product Description

inductive sensor DC



Name	KJ4-M12MB50-DNA
Order number	08310001904
Switching distance	4 mm
Mounting	 shielded
Switch type	 Changeover
Signal Type	DC NPN
Connection	 Cable

Connection diagramm



Dimension (in mm)	fine-pitch thread M12 x 50
-------------------	----------------------------

Technical Specification

Operating voltage	10 - 30 VDC
Max. ripple	$\leq 10 \%$
Voltage drop	2,4 V
Max. load current	200 mA
No load current	$\leq 13 \text{ mA}$
Leakage current	$\leq 10 \mu\text{A}$
Switching frequency	1000 Hz
Switching hysteresis	$\leq 15 \%$
Operating temperature	-25 ° C to 70 ° C

Temperature drift	≤ 10 %
Repeat accuracy	≤ 5 %
Switching state	LED
Time delay	100 ms
Short-circuit proof	yes
Overload protection	yes
Reverse voltage protection	yes
Protection category	IP67
EMC-level	DIN EN 60947-5-2: 2008
Housing material	Brass, nickel plated
Material active face	Pocan KU 2-7503/1 + Batch RAL 9004
Cable length	2 m
Utilisation category	DC 13
Cable material	PVC LIYY grau (grey)
Cable cross	4x0.34 mm ²
FIT / MTTF acc. to SIEMENS 29500	66,97 / 1705y

Errors and omissions excepted