





Capacitive Sensors Series 95 - AC / DC - Relay output

Housing M 32 x 1.5

- Housing material: POM
- Sensing distance 2...25 mm adjustable
- Normally open and normally closed function
- One potential-free change-over contact
- Switch-on delay adjustable 1 sec - 10 min.



Technical data	Non-flush mountable
Level sensor, in contact with the product	Medium dependent adjustable
Operating distance min. / max. adjustable	2...25 mm
Electrical version	5-wire AC / DC
Output	Relay, 1 CO
Type	KAS-95-35-1CO-M32-POM-OND-Z02-1-HP
Art.-No.	KA 0745
Operating voltage (U_B)	20...250 V AC / DC
Load max. AC (I, U, P)	2 A, 250 V, 60 VA
Load max. DC (I, U, P)	2 A, 220 V, 60 W
No-load current (I_o)	2,1 mA
Frequency of operating cycles max.	2 Hz
Permitted ambient temperature	-25...+70 °C
LED-display	Yellow
Protective circuit	Built-in
Degree of protection IEC 60529	IP 67*
Norm	EN 60947-5-2
Connection cable	2 m, PVC, 5 x 0.34 mm ²
Housing material	POM
Active surface	POM
Lid	PBT
Accessories (supplied with the sensor):	2 nuts M 32 x 1,5
Accessories (not supplied with the sensor): Control tube and sensor holder please see our selection of accessories.	



*With sealed potentiometer

Made in Germany